



#	Category	Command	Purpose
1	Access	<code>p4 login</code>	Log in to the Helix Core Server by obtaining a ticket
2		<code>p4 client <name></code>	Create or edit a client workspace specification and its view
3		<code>p4 client -d <name></code>	Delete the workspace with the given name
4		<code>p4 clients</code>	Display list of known clients
5	Sync	<code>p4 sync</code>	Synchronize the client workspace with its view of the depot
6		<code>p4 sync <file>#2</code>	Copy the 2nd revision of the given file to the workspace
7		<code>p4 sync @<label></code>	Sync the workspace with the files and revisions in the label
8		<code>p4 have</code>	List files and revisions that are synced to the client workspace
9		<code>p4 flush</code>	Update a client workspace's have list without copying any files from the depot
10		<code>p4 clean</code>	Delete or refresh local files to match the depot state
11		<code>p4 reconcile</code>	Reconcile a workspace with changes made outside of the Helix Server
12		<code>p4 update</code>	Update a client workspace without overwriting files that have changed since last sync
13	Develop	<code>p4 status</code>	Reports which files need to be added, opened, or deleted
14		<code>p4 change</code>	Create or edit a changelist description
15		<code>p4 changes</code>	Display list of pending and submitted changelists
16		<code>p4 print <file></code>	Retrieve a depot file to the standard output
17		<code>p4 add -c <changelist> <file></code>	Open a new file to add it to the depot
18		<code>p4 edit -c <changelist> <file></code>	Open an existing file for edit
19		<code>p4 lock <file></code>	Lock an opened file against other users submitting changes to the file
20		<code>p4 lock -c <changelist></code>	Lock only files included in changelist
21		<code>p4 unlock <file></code>	Release a locked file but leave it open
22		<code>p4 revert -c <changelist> <file></code>	Discard changes from an opened file
23		<code>p4 delete -c <changelist> <file></code>	Open an existing file for deletion
24		<code>p4 opened -c <changelist></code>	List files that are open in pending changelists
25		<code>p4 undo</code>	Undo a range of revisions
26		<code>p4 undo @<changelist></code>	Undo the effects of a particular change
27		<code>p4 reopen -c <changelist> <file></code>	Change the type or changelist number of an opened file
28		<code>p4 diff <file></code>	Display diff of client file with depot file
29		<code>p4 describe <changelist></code>	View details of a changelist
30		<code>p4 submit</code>	Submit the default changelist files to the depot
31		<code>p4 submit -c <changelist></code>	Submit the given changelist files to the depot
32	Merge	<code>p4 branches</code>	Create or edit a branch specification
33		<code>p4 branches</code>	Display list of branches
34		<code>p4 merge</code>	Merge one set of files (and/or the stream spec) into another
35		<code>p4 copy</code>	Copy files from one location in the depot to another
36		<code>p4 move <file1> <file2></code>	Move (rename) a file from one location to another within the branch
37		<code>p4 rename <file1> <file2></code>	Alias of move command. Move a file from one location to another
38		<code>p4 resolve</code>	Merge open files (scheduled for resolve) with other revisions or files
39		<code>p4 resolved</code>	Show files that have been merged but not submitted
40	Shelve	<code>p4 shelve -c <changelist></code>	Store files from a pending changelist in the depot, without submitting them
41		<code>p4 unshelve -c <changelist></code>	Restore shelved files from a pending change into a workspace
42		<code>p4 reshelve -c <changelist></code>	Copy shelved files from an existing shelf into either a new shelf or into an existing one
43	Label	<code>p4 list -l <label> <filespec></code>	Create a list of files that can be used as a label
44		<code>p4 label <name></code>	Create a new label specification or edit an existing label specification
45		<code>p4 labels</code>	Display the list of defined labels
46		<code>p4 tag -l <label></code>	Tag files with a label